

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Bonding
- > Wrapping
- > Temp. Fixing
- > Reinforcing
- > Many more ...

ADVANTAGES AND BENEFITS

- > Strong
- > UV Resistant
- > Waterproof
- > All-Weather

CONSTRUCTION

Overall Grade: General Purpose Cloth Tape
Backing: Synthetic Cloth Laminated
Adhesive: Non-solvent, specially modified UV stable adhesive

COLOR(S)

■ Silver ■ Black □ White

STANDARD SIZE

Width(s): 48mm / 2"
Length(s): 27m / 30yd, 55m / 60yd

Contact your Dolphin sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	230	my	(+/- 10%)
Adhesion to Stainless Steel 180°	≥ 15	N/2,5cm	-
Tensile Strength	30	N/cm	(+/- 5%)
Service Temperature Range	-30	minimum °C	-
	60	max °C	-



The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.